NSN 5905-01-103-7535

Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-103-7535

Towns of the Conflict of Conflict of the Conflict of C
Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-100.0/+100.0
Electrical Resistance:
470.000 ohms
Resistance Tolerance In Percent:
-2.000/+2.000
Ambient Tempurature In Deg Celsius At Full Rated Power:
70.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
130.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-55.0/+125.0
Inclosure Method:
Encapsulated
Terminal Quantity:
16
Terminal Type:
Tab, solder lug
Reliability Indicator:
Not established
Terminal Length:
remina Lengan.
Between 0.110 inches and 0.140 inches
-
Between 0.110 inches and 0.140 inches
Between 0.110 inches and 0.140 inches Body Length:
Between 0.110 inches and 0.140 inches Body Length: 0.845 inches
Between 0.110 inches and 0.140 inches Body Length: 0.845 inches Body Width:
Between 0.110 inches and 0.140 inches Body Length: 0.845 inches Body Width: 0.245 inches
Between 0.110 inches and 0.140 inches Body Length: 0.845 inches Body Width: 0.245 inches Body Height:
Between 0.110 inches and 0.140 inches Body Length: 0.845 inches Body Width: 0.245 inches Body Height: 0.100 inches
Between 0.110 inches and 0.140 inches Body Length: 0.845 inches Body Width: 0.245 inches Body Height: 0.100 inches Schematic Diagram Designator:
Between 0.110 inches and 0.140 inches Body Length: 0.845 inches Body Width: 0.245 inches Body Height: 0.100 inches Schematic Diagram Designator: Ladder network
Between 0.110 inches and 0.140 inches Body Length: 0.845 inches Body Width: 0.245 inches Body Height: 0.100 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts: 1.800 total network
Between 0.110 inches and 0.140 inches Body Length: 0.845 inches Body Width: 0.245 inches Body Height: 0.100 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts:
Between 0.110 inches and 0.140 inches Body Length: 0.845 inches Body Width: 0.245 inches Body Height: 0.100 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts: 1.800 total network Identical Value Resistor Quantity: 15 each resistor
Between 0.110 inches and 0.140 inches Body Length: 0.845 inches Body Width: 0.245 inches Body Height: 0.100 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts: 1.800 total network Identical Value Resistor Quantity:
Between 0.110 inches and 0.140 inches Body Length: 0.845 inches Body Width: 0.245 inches Body Height: 0.100 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts: 1.800 total network Identical Value Resistor Quantity: 15 each resistor Style Designator:
Between 0.110 inches and 0.140 inches Body Length: 0.845 inches Body Width: 0.245 inches Body Height: 0.100 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts: 1.800 total network Identical Value Resistor Quantity: 15 each resistor Style Designator: Dual inline
Between 0.110 inches and 0.140 inches Body Length: 0.845 inches Body Width: 0.245 inches Body Height: 0.100 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts: 1.800 total network Identical Value Resistor Quantity: 15 each resistor Style Designator: Dual inline Shelf Life:
Between 0.110 inches and 0.140 inches Body Length: 0.845 inches Body Width: 0.245 inches Body Height: 0.100 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts: 1.800 total network Identical Value Resistor Quantity: 15 each resistor Style Designator: Dual inline Shelf Life: N/a

No

NSN 5905-01-103-7535

Film Fixed Resistor Network - Page 2 of 2



Fiig:

A001a0