# NSN 5905-01-104-0587

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-104-0587 **Section Quantity: Body Style:** Cylindrical bushing mounted **Body Diameter:** 0.500 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.625 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 0.531 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 298.0 **Maximum Starting Torque:** 6.00 inch-ounces **Maximum Running Torque:** 6.00 inch-ounces **Maximum Stop Torque:** 48.00 inch-ounces **Nonturn Device Location:** At 4 oclock and at 10 oclock **Nonturn Device Radius:** 0.245 inches **Screw Thread Diameter:** 0.250 inches **Screw Thread Series Designator:** 

Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Rear end **Mounting Method:** Shaft w/panel seal **Electrical Resistance Per Section:** 5.000 megohms single section

## NSN 5905-01-104-0587

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Rotary	Actuator	Travel In	<b>Angular</b>	Deg:

298.0

## **Resistance Tempurature Characteristic Range Per Section In Percent:**

-3.0/+0.0 -55 degrees celsius single section and -5.0/+10.0 -25 degrees celsius single section and -5.0/+10.0 25 degrees celsius single section and +0.0/+3.0 120 degrees celsius single section

## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 single section

## **Power Dissipation Rating Per Section In Watts:**

0.5 free air single section

#### **Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

#### **Actuator Travel Control Feature:**

Stops

## Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

## **Standard Taper Curve Per Section:**

A single section

#### **Test Data Document:**

81349-mil-r-94/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Terminal Type And Quantity:**

3 tab, solder lug

Shelf Life: N/a

Unit Of Measure:

--

**Demilitarization:** 

No

Fiig:

A002a0