NSN 5905-01-104-2120

Film Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-104-2120
Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-200.0/+200.0 first temp coefficient
Electrical Resistance:
1.500 kilohms
Resistance Tolerance In Percent:
-1.000/+1.000
Ambient Tempurature In Deg Celsius At Full Rated Power:
70.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
150.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-55.0/+150.0 temp range of first temp coefficient
Inclosure Method:
Encapsulated
Terminal Type:
Wire lead
Reliability Indicator:
Established
Reliability Failure Rate Level In Percent:
0.001
Body Diameter:
0.066 inches
Body Length:
0.150 inches
Power Dissipation Rating In Watts:
0.125 free air
Nuclear Hardness Critical Feature:
Hardened
Style Designator:
Axial terminal each end
Test Data Document:
81349-mil-prf-39017/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-prf-39017/5 government specification
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No

A001a0

Fiig:

NSN 5905-01-104-2120

Film Fixed Resistor - Page 2 of 2



Mil-std (military Standard):

Mil-prf-39017 spec.