NSN 5905-01-104-8378

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-104-8378 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:**

0.344 inches Flat Height: 0.216 inches

1.750 inches

First Flat Length:

Body Diameter: 1.156 inches **Shaft Diameter:** 0.250 inches

Shaft Length: 0.750 inches

Mounting Bushing Length:

0.375 inches

Body Length:

0.812 inches

Overall Diameter:

1.750 inches

Shaft Style:

Round, flatted

Switch Type:

Rotary

Switch Voltage Rating In Volts:

125.0

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

292.0

Maximum Starting Torque:

9.00 inch-ounces

Maximum Running Torque:

9.00 inch-ounces

Maximum Stop Torque:

192.00 inch-ounces

Nonturn Device Location:

At 9 oclock

NSN 5905-01-104-8378

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 3



Nantura Davida Badina	
Nonturn Device Radius: 0.531 inches	
Switch Operating Position:	
Start of rotation	
Switch Contact Arrangement:	
Single pole, single throw, normally open, both positions maintained	
Fragility Factor:	
Moderately rugged	
Screw Thread Diameter:	
0.375 inches	
Screw Thread Series Designator:	
Unef	
Screw Thready Qty Per Inch (tpi):	
32.0	
Terminal Location:	
Rear-bottom	
Mounting Method:	
Standard bushing	
Features Provided:	
Switch	
Electrical Resistance Per Section:	
2.500 kilohms single section	
Rotary Actuator Travel In Angular Deg:	
333.0	
Resistance Tempurature Characteristic Range Per Section In Percent:	
+0.0/+6.9 -55 degrees celsius single section and +0.0/+5.6 120 degrees celsius single section	
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:	
120.0 single section	
Power Dissipation Rating Per Section In Watts:	
2.25 free air single section	
Resistance Tolerance Per Section In Percent:	
-10.0/+10.0 single section	
Actuator Travel Control Feature:	
Stops	
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	
70.0 single section	
Switch Current Type And Rating In Amps:	
2.000 ac	
Standard Taper Curve Per Section:	
A single section	
Terminal Type And Quantity:	
5 tab, solder lug	
Shelf Life:	
N/a	

NSN 5905-01-104-8378

Nonprecision Nonwire Wound Variable Resistor - Page 3 of 3



		• -						
	In		Of	RЛ	മാ	CI	ır	Δ.
L	,,,			IVI	ca			

--

Demilitarization:

No

Fiig:

A002a0