

View Online at <https://aerobasegroup.com/nsn/5905-01-105-4028>

**Section Quantity:**

1

**Body Style:**

Rectangular w/mounting holes/slots

**Reliability Indicator:**

Established

**Reliability Failure Rate Level In Percent:**

0.005

**Terminal Length:**

0.531 inches

**Mounting Hole Diameter:**

0.098 inches

**Shaft Diameter:**

0.130 inches

**Shaft Length:**

0.070 inches

**Body Length:**

Between 1.240 inches and 1.260 inches

**Body Width:**

Between 0.190 inches and 0.200 inches

**Body Height:**

Between 0.320 inches and 0.330 inches

**Shaft Style:**

Round

**Actuator Type:**

Single shaft

**Center To Center Distance Between Terminals:**

0.910 inches

**End Application:**

M1, m1a1, thermal electronics unit thermal system test set m1

**Lateral Distance Between Mounting Hole Centers:**

Between 0.990 inches and 1.010 inches

**Mounting Facility Quantity:**

2

**Terminal Location:**

Lower adjacent side single row

**Mounting Method:**

Unthreaded hole

**Electrical Resistance Per Section:**

20.0 kilohms single section

**Center To Center Distance Between Center Terminal And Outside Terminal:**

0.710 inches

**Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:**

-10.0/+10.0 single section

**Power Dissipation Rating Per Section In Watts:**

0.5 free air single section

**Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 single section

**Precious Material And Location:**

Terminal surfaces gold

**Precious Material:**

Gold

**Terminal Type And Quantity:**

3 pin

**Specification Data:**

19200-12272048 manufacturers source control

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0