

View Online at <https://aerobasegroup.com/nsn/5905-01-105-4028>

Section Quantity:

1

Body Style:

Rectangular w/mounting holes/slots

Reliability Indicator:

Established

Reliability Failure Rate Level In Percent:

0.005

Terminal Length:

0.531 inches

Mounting Hole Diameter:

0.098 inches

Shaft Diameter:

0.130 inches

Shaft Length:

0.070 inches

Body Length:

Between 1.240 inches and 1.260 inches

Body Width:

Between 0.190 inches and 0.200 inches

Body Height:

Between 0.320 inches and 0.330 inches

Shaft Style:

Round

Actuator Type:

Single shaft

Center To Center Distance Between Terminals:

0.910 inches

End Application:

M1, m1a1, thermal electronics unit thermal system test set m1

Lateral Distance Between Mounting Hole Centers:

Between 0.990 inches and 1.010 inches

Mounting Facility Quantity:

2

Terminal Location:

Lower adjacent side single row

Mounting Method:

Unthreaded hole

Electrical Resistance Per Section:

20.0 kilohms single section

Center To Center Distance Between Center Terminal And Outside Terminal:

0.710 inches

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-10.0/+10.0 single section

Power Dissipation Rating Per Section In Watts:

0.5 free air single section

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 single section

Precious Material And Location:

Terminal surfaces gold

Precious Material:

Gold

Terminal Type And Quantity:

3 pin

Specification Data:

19200-12272048 manufacturers source control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0