NSN 5905-01-105-8051

Section Quantity:

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 3

View Online at https://aerobasegroup.com/nsn/5905-01-105-8051



Body Style: Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 1.036 inches **Shaft Diameter:** Between 0.248 inches and 0.250 inches **Shaft Length:** 1.375 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 1.560 inches **Undercut Diameter:** 0.125 inches **Shaft Style:** Round, stepped Switch Type: Push-pull **Switch Voltage Rating In Volts:** 115.0 and 28.0 **Actuator Type:** Dual concentric **Effective Electrical Rotation In Deg Angular Rotation:** 285.0 **Maximum Starting Torque:** 3.00 inch-ounces **Maximum Running Torque:** 3.00 inch-ounces **Nonturn Device Location:** At 3 oclock **Nonturn Device Radius:** 0.437 inches **Switch Operating Position:** Any position of rotation travel **Switch Contact Arrangement:** One pole 10 position non-shorting contact switch **Fragility Factor:** Moderately rugged

NSN 5905-01-105-8051

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 3



Undercut Length:
0.875 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over more than half the circumference
Mounting Method:
Standard bushing
Features Provided:
Switch
Electrical Resistance Per Section:
1.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
300.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
110.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-100.0/+100.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Switch Current Type And Rating In Amps:
2.000 ac/dc
Standard Taper Curve Per Section:
A single section
Special Features:
Smaller shaft flatted 0.250 in. Lg by 0.093 in. Height
Terminal Type And Quantity:
14 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 5905-01-105-8051

Nonprecision Nonwire Wound Variable Resistor - Page 3 of 3



Fiig:

A002a0