

View Online at <https://aerobasegroup.com/nsn/5905-01-106-0678>

**Section Quantity:**

1

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**Shaft Diameter:**

0.250 inches

**Shaft Length:**

0.625 inches

**Mounting Bushing Length:**

0.500 inches

**Shaft Style:**

Round, slotted

**Actuator Type:**

Single shaft

**Nonturn Device Location:**

At 9 oclock

**Nonturn Device Radius:**

0.375 inches

**Fragility Factor:**

Rugged

**Screw Thread Diameter:**

0.375 inches

**Screw Thread Series Designator:**

Unef

**Screw Thready Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Locking bushing

**Features Provided:**

Shaft locking device

**Electrical Resistance Per Section:**

200.0 kilohms single section

**Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

**Criticality Code Justification:**

Feat

**Standard Taper Curve Per Section:**

A single section

**Special Features:**

Item must comply with requirements of defense electronics supply center production standard no. L02976; for navy nuclear propulsion plant products only

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0