

View Online at <https://aerobasegroup.com/nsn/5905-01-107-1914>

Section Quantity:

2

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

0.7500 inches

Pilot Length:

0.0620 inches

Undercut Diameter:

0.875 inches

Undercut Width:

0.0620 inches

Body Diameter:

0.875 inches

Shaft Diameter:

0.125 inches

Shaft Length:

0.438 inches

Body Length:

0.836 inches

Mounting Lip Diameter:

0.8750 inches

Mounting Lip Depth:

0.0620 inches

Shaft Style:

Round

Shaft Bearing Type:

Ball

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

350.0

Maximum Starting Torque:

0.10 inch-ounces

Maximum Running Torque:

0.10 inch-ounces

Shaft End Play:

0.00300 inches

Shaft Runout:

0.001 inches

Lateral Runout:

0.002 inches

Pilot Diameter Runout:

0.00150 inches

Shaft Radial Play:

0.002 inches

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Shaft

Electrical Resistance Per Section:

2000.000 ohms c and better industrial clears

Rotary Actuator Travel In Angular Deg:

360.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 all sections

Power Dissipation Rating Per Section In Watts:

1.0 free air all sections

Resistance Tolerance Per Section In Percent:

-3.0/+3.0 all sections

Actuator Travel Control Feature:

Continuous motion

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 all sections

Standard Taper Curve Per Section:

A all sections

Terminal Type And Quantity:

6 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0