## NSN 5905-01-107-2293

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-107-2293

Section Quantity:
1
Body Style:
Rectangular
Reliability Indicator:
Not established
Terminal Length:
0.200 inches
Body Length:
0.190 inches
Body Width:
0.375 inches
Body Height:
0.375 inches
Actuator Type:
Flush drive with slot-hole
Effective Electrical Rotation In Deg Angular Rotation:
280.0
Maximum Starting Torque:
5.00 inch-ounces
Maximum Running Torque:
5.00 inch-ounces
5.00 inch-ounces  Center To Center Distance Between Terminals:
Center To Center Distance Between Terminals:
Center To Center Distance Between Terminals: 0.300 inches
Center To Center Distance Between Terminals:  0.300 inches  Fragility Factor:
Center To Center Distance Between Terminals:  0.300 inches  Fragility Factor:  Moderately delicate
Center To Center Distance Between Terminals:  0.300 inches  Fragility Factor:  Moderately delicate  Terminal Location:
Center To Center Distance Between Terminals:  0.300 inches  Fragility Factor:  Moderately delicate  Terminal Location:  Lower adjacent side single row
Center To Center Distance Between Terminals:  0.300 inches  Fragility Factor:  Moderately delicate  Terminal Location:  Lower adjacent side single row  Mounting Method:
Center To Center Distance Between Terminals:  0.300 inches  Fragility Factor:  Moderately delicate  Terminal Location:  Lower adjacent side single row  Mounting Method:  Terminal
Center To Center Distance Between Terminals:  0.300 inches  Fragility Factor:  Moderately delicate  Terminal Location:  Lower adjacent side single row  Mounting Method:  Terminal  Electrical Resistance Per Section:
Center To Center Distance Between Terminals:  0.300 inches  Fragility Factor:  Moderately delicate  Terminal Location:  Lower adjacent side single row  Mounting Method:  Terminal  Electrical Resistance Per Section:  50.000 kilohms single section
Center To Center Distance Between Terminals:  0.300 inches  Fragility Factor:  Moderately delicate  Terminal Location:  Lower adjacent side single row  Mounting Method:  Terminal  Electrical Resistance Per Section:  50.000 kilohms single section  Rotary Actuator Travel In Angular Deg:
Center To Center Distance Between Terminals:  0.300 inches  Fragility Factor:  Moderately delicate  Terminal Location:  Lower adjacent side single row  Mounting Method:  Terminal  Electrical Resistance Per Section:  50.000 kilohms single section  Rotary Actuator Travel In Angular Deg:  360.0
Center To Center Distance Between Terminals:  0.300 inches  Fragility Factor:  Moderately delicate  Terminal Location:  Lower adjacent side single row  Mounting Method:  Terminal  Electrical Resistance Per Section:  50.000 kilohms single section  Rotary Actuator Travel In Angular Deg:  360.0  Center To Center Distance Between Center Terminal And Outside Terminal:
Center To Center Distance Between Terminals:  0.300 inches  Fragility Factor:  Moderately delicate  Terminal Location:  Lower adjacent side single row  Mounting Method:  Terminal  Electrical Resistance Per Section:  50.000 kilohms single section  Rotary Actuator Travel In Angular Deg:  360.0  Center To Center Distance Between Center Terminal And Outside Terminal:  0.150 inches
Center To Center Distance Between Terminals:  0.300 inches  Fragility Factor:  Moderately delicate  Terminal Location:  Lower adjacent side single row  Mounting Method:  Terminal  Electrical Resistance Per Section:  50.000 kilohms single section  Rotary Actuator Travel In Angular Deg:  360.0  Center To Center Distance Between Center Terminal And Outside Terminal:  0.150 inches  Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

0.5 free air single section

**Power Dissipation Rating Per Section In Watts:** 

## NSN 5905-01-107-2293

Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No