## NSN 5905-01-107-5153

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-107-5153 **Section Quantity: Body Style:** Cylindrical w/readout **Reliability Indicator:** Not established **Overall Length:** 1.567 inches **Body Diameter:** 0.875 inches **Body Length:** 1.380 inches **Overall Diameter:** 1.240 inches **Actuator Type:** Integral knob with counter **Effective Electrical Rotation In Deg Angular Rotation:** 3600.0 **Maximum Starting Torque:** 15.00 inch-ounces **Maximum Running Torque:** 15.00 inch-ounces **Nonturn Device Location:** At 12 oclock **Nonturn Device Radius:** 0.498 inches **Fragility Factor:** Rugged **Terminal Location:** Rear end **Mounting Method:** Snap-in **Electrical Resistance Per Section:** 5.0 percent, rated amperes c and better flooring **Rotary Actuator Travel In Angular Deg:** 3600.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 85.0 single section **Power Dissipation Rating Per Section In Watts:** 1.5 7th secondary quality

**Resistance Tolerance Per Section In Percent:** 

-5.0/+5.0 single section

## NSN 5905-01-107-5153

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Actuator Travel Control Feature:
Stops
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
25.0 single section
Standard Taper Curve Per Section:
A single section
Special Features:
Decimal point placed on face of dial; positioned one space from left
Precious Material And Location:
Terminal surfaces gold
Precious Material:
Gold
Terminal Type And Quantity:
3 wire loop
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0