## NSN 5905-01-108-4263

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-108-4263

Section Quantity:
1
Body Style:
Rectangular
Reliability Indicator:
Not established
Overall Length:
0.196 inches
Overall Height:
0.876 inches
Overall Width:
0.594 inches
Body Length:
0.156 inches
Body Width:
0.594 inches
Body Height:
0.735 inches
Actuator Type:
Integral knob
Effective Electrical Rotation In Deg Angular Rotation:
270.0
Maximum Starting Torque:
6.00 inch-ounces
Maximum Running Torque:
6.00 inch-ounces
Maximum Stop Torque:
32.00 inch-ounces
Nonturn Device Location:
At 9 oclock
Fragility Factor:
Moderately rugged
Terminal Location:
Lower adjacent side two rows
Mounting Method:
Terminal
Cubic Measure:
0.068 cubic inches
Electrical Resistance Per Section:
3.0 percent, rated amperes c and better flooring
Rotary Actuator Travel In Angular Deg:

270.0

## NSN 5905-01-108-4263

No Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 85.0 single section **Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:** -400.0/+500.0 single section **Power Dissipation Rating Per Section In Watts:** 0.25 7th secondary quality **Resistance Tolerance Per Section In Percent:** -20.0/+20.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a **Unit Of Measure: Demilitarization:**