Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-108-5139

## Section Quantity:

1

Body Style:

Cylindrical hole/slot mounted

## **Reliability Indicator:**

Not established

## **Overall Length:**

4.188 inches

## Body Diameter:

6.000 inches

## Shaft Diameter:

0.375 inches

## Shaft Length:

2.000 inches

## Body Length:

2.188 inches

## Overall Diameter:

7.376 inches

## Mounting Hole/stud Circle Diameter:

2.375 inches

## Shaft Style:

Round

## Actuator Type:

Single shaft

## Effective Electrical Rotation In Deg Angular Rotation:

317.0

## Maximum Starting Torque:

16.00 inch-ounces

## Maximum Running Torque:

16.00 inch-ounces

## Screw Thread Diameter:

0.250 inches

## Screw Thread Series Designator:

Unc

# Screw Thready Qty Per Inch (tpi):

20.0

## Mounting Facility Quantity:

2

# **Terminal Location:**

Radially positioned over less than half the circumference

# Mounting Method:

Threaded hole

# NSN 5905-01-108-5139

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



**Electrical Resistance Per Section:** 28.0 ohms single section **Rotary Actuator Travel In Angular Deg:** 317.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 340.0 single section **Power Dissipation Rating Per Section In Watts:** 300.0 free air single section **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section **Actuator Travel Control Feature:** Stops Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section Standard Taper Curve Per Section: A single section **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A002a0