NSN 5905-01-108-6809

Film Fixed Resistor - Page 1 of 2

-100.0 to 100.0

5.900 kilohms

Electrical Resistance:

Resistance Tolerance In Percent:



View Online at https://aerobasegroup.com/nsn/5905-01-108-6809

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

No
Demilitarization:
Unit Of Measure:
N/a
Shelf Life:
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
81349-mil-r-39017/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format: excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Test Data Document: 21240 mil r 20017/5 appoilipation (includes angineering type bulleting, breekures, etc., that reflect appoilipation type data in appoilipation.
Axial terminal each end Test Pata Pagument:
Style Designator:
0.3 grams Style Designatory
Unpackaged Unit Weight:
0.125 free air
Power Dissipation Rating In Watts:
Between 0.130 inches and 0.187 inches
Body Length:
Between 0.058 inches and 0.074 inches
Body Diameter: Petwoon 0.059 inches and 0.074 inches
Between 1.000 inches and 1.625 inches
Terminal Length: Return 1 000 inches and 1 005 inches
0.100 Towning I Longth
Reliability Failure Rate Level In Percent:
Established Policibility Foilure Rate Level In Percent
Reliability Indicator:
C Polichility Indicators
Mil-std-1276 Wire Lead Type Designator:
Wire lead
Terminal Type:
Encapsulated Township LT was
Inclosure Method:
-55.0 to 150.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
150.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
70.0
Ambient Tempurature In Deg Celsius At Full Rated Power:
-1.000 to 1.000

NSN 5905-01-108-6809

Film Fixed Resistor - Page 2 of 2



Fiig:

A001a0