NSN 5905-01-109-0583

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-109-0583

Section Oceantitus
Section Quantity:
1 Partic Studen
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
1.094 inches
Shaft Diameter:
0.250 inches
Shaft Length:
1.625 inches
Mounting Bushing Length:
0.375 inches
Body Length:
0.562 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
312.0
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
1.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
312.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

NSN 5905-01-109-0583

A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Actuator Travel Control Feature:	
Stops	
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	
70.0 single section	
Standard Taper Curve Per Section:	
A single section	
Terminal Type And Quantity:	
3 tab, solder lug	
Shelf Life:	
N/a	
Unit Of Measure:	
-	
Demilitarization:	
No	
Filg:	