Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-109-2155

## Section Quantity:

1

Body Style:

Rectangular

# **Reliability Indicator:**

Not established

## **Overall Length:**

0.190 inches

#### Terminal Length:

0.200 inches

#### **Overall Height:**

0.565 inches

#### **Overall Width:**

0.375 inches

#### Body Length:

### 0.190 inches

# Body Width:

0.375 inches

# Body Height:

0.375 inches

### Actuator Type:

Flush drive with slot-hole

### Effective Electrical Rotation In Deg Angular Rotation:

280.0

### Maximum Starting Torque:

5.00 inch-ounces

### Maximum Running Torque:

5.00 inch-ounces

### Center To Center Distance Between Terminals:

0.300 inches

### **Terminal Location:**

Lower adjacent side single row

### **Mounting Method:**

Terminal

### **Features Provided:**

Humidity proof

### **Electrical Resistance Per Section:**

200.000 ohms single section

## **Rotary Actuator Travel In Angular Deg:**

280.0

### Center To Center Distance Between Center Terminal And Outside Terminal:

0.150 inches



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -100.0/+100.0 single section **Power Dissipation Rating Per Section In Watts:** 0.5 free air single section **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 85.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 pin Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A002a0