## NSN 5905-01-109-4102

Dual inline

Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-109-4102

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-100.0/+100.0
Electrical Resistance:
3.900 kilohms
Resistance Tolerance In Percent:
-2.000/+2.000
Ambient Tempurature In Deg Celsius At Full Rated Power:
70.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
125.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-55.0/+125.0
Inclosure Method:
Encapsulated Encapsulated
Terminal Quantity:
14
Terminal Type:
Pin
Reliability Indicator:
Not established
Terminal Length:
0.135 inches
Body Length:
0.740 inches
Body Width:
0.270 inches
Body Height:
0.200 inches
Schematic Diagram Designator:
Isolated array
Power Dissipation Rating In Watts:
1.400 total network
End Application:
Helecopter, search and rescue, hh-60h; aircraft, tomcat f-14, helicopter, ch-53a/d/e; helicopter, lamps marks iii, sh-60b; helicopter,
mh-53e; missile, lance
Identical Value Resistor Quantity:
7 each resistor
Criticality Code Justification:
Feat
Special Features:
Weapon system essential
Style Designator:

## NSN 5905-01-109-4102

Film Fixed Resistor Network - Page 2 of 2



## **Test Data Document:**

81349-mil-prf-83401/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

81349-mil-prf-83401/1	government specification
-----------------------	--------------------------

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A001a0

Mil-std (military Standard):

Mil-prf-83401 spec.