NSN 5905-01-110-1687

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-110-1687 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** Between 2.241 inches and 2.311 inches **Body Diameter:** Between 0.860 inches and 0.890 inches **Shaft Diameter:** Between 0.248 inches and 0.250 inches **Shaft Length:** Between 0.782 inches and 0.842 inches **Mounting Bushing Length:** Between 0.297 inches and 0.327 inches **Body Length:** Between 1.459 inches and 1.469 inches **Overall Diameter:** Between 0.860 inches and 0.890 inches **Shaft Style:** Round **Shaft Bearing Type:** Sleeve **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3610.0 **Maximum Starting Torque:** 2.00 inch-ounces **Maximum Running Torque:** 2.00 inch-ounces **Maximum Stop Torque:** 60.00 inch-ounces **Shaft End Play:** 0.015 inches **Shaft Radial Play:** 0.005 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:**

Unef

NSN 5905-01-110-1687

Precision Wire Wound Variable Resistor - Page 2 of 2



| Screw Thready Qty Per Inch (tpi): |
|--|
| 32.0 |
| Terminal Location: |
| Longitudinally positioned on the circumference |
| Mounting Method: |
| Standard bushing |
| Features Provided: |
| Humidity proof |
| Electrical Resistance Per Section: |
| 10.0 ohms single section |
| Rotary Actuator Travel In Angular Deg: |
| 3600.0 |
| Function Conformity Tolerance Per Section: |
| -0.25/+0.25 single section |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
| 85.0 single section |
| Power Dissipation Rating Per Section In Watts: |
| 2.0 free air single section |
| Function Conformity Per Section: |
| Single section independent linearity |
| Resistance Tolerance Per Section In Percent: |
| -5.0/+5.0 single section |
| Actuator Travel Control Feature: |
| Clutch |
| Function Characteristic Per Section: |
| Single section linear |
| Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: |
| +0.0/+800.0 single section |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: |
| 25.0 single section |
| Terminal Type And Quantity: |
| 3 turret |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Filig: |
| A002a0 |
| |