NSN 5905-01-110-1687

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-110-1687 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** Between 2.241 inches and 2.311 inches **Body Diameter:** Between 0.860 inches and 0.890 inches **Shaft Diameter:** Between 0.248 inches and 0.250 inches **Shaft Length:** Between 0.782 inches and 0.842 inches **Mounting Bushing Length:** Between 0.297 inches and 0.327 inches **Body Length:** Between 1.459 inches and 1.469 inches **Overall Diameter:** Between 0.860 inches and 0.890 inches **Shaft Style:** Round **Shaft Bearing Type:** Sleeve **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3610.0 **Maximum Starting Torque:** 2.00 inch-ounces **Maximum Running Torque:** 2.00 inch-ounces **Maximum Stop Torque:** 60.00 inch-ounces **Shaft End Play:** 0.015 inches **Shaft Radial Play:** 0.005 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:**

Unef

NSN 5905-01-110-1687

Precision Wire Wound Variable Resistor - Page 2 of 2



Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Longitudinally positioned on the circumference
Mounting Method:
Standard bushing
Features Provided:
Humidity proof
Electrical Resistance Per Section:
10.0 ohms single section
Rotary Actuator Travel In Angular Deg:
3600.0
Function Conformity Tolerance Per Section:
-0.25/+0.25 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
85.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Clutch
Function Characteristic Per Section:
Single section linear
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
+0.0/+800.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
25.0 single section
Terminal Type And Quantity:
3 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Filig:
A002a0