NSN 5905-01-110-2814

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-110-2814

Section Quantity:
1
Body Style:
Rectangular
Reliability Indicator:
Not established
Terminal Length:
0.188 inches
Body Length:
0.190 inches
Body Width:
0.360 inches
Body Height:
0.360 inches
Actuator Type:
Flush drive with slot-hole
Effective Electrical Rotation In Deg Angular Rotation:
270.0
Maximum Starting Torque:
5.00 inch-ounces
Maximum Running Torque:
5.00 inch-ounces
5.00 inch-ounces Center To Center Distance Between Terminals:
Center To Center Distance Between Terminals:
Center To Center Distance Between Terminals: 0.200 inches
Center To Center Distance Between Terminals: 0.200 inches Terminal Location:
Center To Center Distance Between Terminals: 0.200 inches Terminal Location: Lower adjacent side single row
Center To Center Distance Between Terminals: 0.200 inches Terminal Location: Lower adjacent side single row Mounting Method:
Center To Center Distance Between Terminals: 0.200 inches Terminal Location: Lower adjacent side single row Mounting Method: Terminal
Center To Center Distance Between Terminals: 0.200 inches Terminal Location: Lower adjacent side single row Mounting Method: Terminal Features Provided:
Center To Center Distance Between Terminals: 0.200 inches Terminal Location: Lower adjacent side single row Mounting Method: Terminal Features Provided: Humidity proof
Center To Center Distance Between Terminals: 0.200 inches Terminal Location: Lower adjacent side single row Mounting Method: Terminal Features Provided: Humidity proof Electrical Resistance Per Section:
Center To Center Distance Between Terminals: 0.200 inches Terminal Location: Lower adjacent side single row Mounting Method: Terminal Features Provided: Humidity proof Electrical Resistance Per Section: 200.000 ohms single section
Center To Center Distance Between Terminals: 0.200 inches Terminal Location: Lower adjacent side single row Mounting Method: Terminal Features Provided: Humidity proof Electrical Resistance Per Section: 200.000 ohms single section Rotary Actuator Travel In Angular Deg:
Center To Center Distance Between Terminals: 0.200 inches Terminal Location: Lower adjacent side single row Mounting Method: Terminal Features Provided: Humidity proof Electrical Resistance Per Section: 200.000 ohms single section Rotary Actuator Travel In Angular Deg: 300.0
Center To Center Distance Between Terminals: 0.200 inches Terminal Location: Lower adjacent side single row Mounting Method: Terminal Features Provided: Humidity proof Electrical Resistance Per Section: 200.000 ohms single section Rotary Actuator Travel In Angular Deg: 300.0 Center To Center Distance Between Center Terminal And Outside Terminal:
Center To Center Distance Between Terminals: 0.200 inches Terminal Location: Lower adjacent side single row Mounting Method: Terminal Features Provided: Humidity proof Electrical Resistance Per Section: 200.000 ohms single section Rotary Actuator Travel In Angular Deg: 300.0 Center To Center Distance Between Center Terminal And Outside Terminal: 0.100 inches
Center To Center Distance Between Terminals: 0.200 inches Terminal Location: Lower adjacent side single row Mounting Method: Terminal Features Provided: Humidity proof Electrical Resistance Per Section: 200.000 ohms single section Rotary Actuator Travel In Angular Deg: 300.0 Center To Center Distance Between Center Terminal And Outside Terminal: 0.100 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

0.5 free air single section

Power Dissipation Rating Per Section In Watts:

NSN 5905-01-110-2814

Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section In Percent:
-20.0/+20.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No