NSN 5905-01-111-0611

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-111-0611

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
1.937 inches
Body Diameter:
0.875 inches
Shaft Diameter:
Between 0.2494 inches and 0.2497 inches
Shaft Length:
0.812 inches
Mounting Bushing Length:
0.312 inches
Body Length:
1.125 inches
Overall Diameter:
1.078 inches
Shaft Style:
Round
Shaft Bearing Type:
Bearing
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
3600.0
Maximum Running Torque:
2.00 inch-ounces
Nonturn Device Location:
At 12 oclock
Nonturn Device Radius:
0.290 inches
Fragility Factor:
Rugged
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):

32.0

NSN 5905-01-111-0611

Precision Wire Wound Variable Resistor - Page 2 of 2



Terminal Location:
Longitudinally positioned on the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
15.0 percent, rated amperes c and better flooring
Rotary Actuator Travel In Angular Deg:
3600.0
Function Conformity Tolerance Per Section:
-0.25/+0.25 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
105.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 7th secondary quality
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
7 oclock all primaries
7 oclock all primaries Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
·
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 25.0 single section
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 25.0 single section Precious Material And Location:
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 25.0 single section Precious Material And Location: Terminal surfaces gold
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 25.0 single section Precious Material And Location: Terminal surfaces gold Precious Material:
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 25.0 single section Precious Material And Location: Terminal surfaces gold Precious Material: Gold
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 25.0 single section Precious Material And Location: Terminal surfaces gold Precious Material: Gold Terminal Type And Quantity:
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 25.0 single section Precious Material And Location: Terminal surfaces gold Precious Material: Gold Terminal Type And Quantity: 3 tab, solder lug
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 25.0 single section Precious Material And Location: Terminal surfaces gold Precious Material: Gold Terminal Type And Quantity: 3 tab, solder lug Shelf Life:
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 25.0 single section Precious Material And Location: Terminal surfaces gold Precious Material: Gold Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 25.0 single section Precious Material And Location: Terminal surfaces gold Precious Material: Gold Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 25.0 single section Precious Material And Location: Terminal surfaces gold Precious Material: Gold Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure:
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 25.0 single section Precious Material And Location: Terminal surfaces gold Precious Material: Gold Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: