Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-111-4482

Section Quantity:

1

Body Style:

Cylindrical

Reliability Indicator:

Not established

Terminal Length:

0.187 inches

Body Diameter:

0.562 inches

Body Length:

0.325 inches

Actuator Type:

Integral knob

Effective Electrical Rotation In Deg Angular Rotation:

320.0

Maximum Starting Torque:

7.50 inch-ounces

Maximum Running Torque:

7.50 inch-ounces

Center To Center Distance Between Terminals:

0.200 inches

Terminal Location:

Rear end

Mounting Method:

Terminal

Electrical Resistance Per Section:

5.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

360.0

Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-150.0/+150.0 single section

Power Dissipation Rating Per Section In Watts:

0.75 free air single section

Resistance Tolerance Per Section In Percent:

-20.0/+20.0 single section

Actuator Travel Control Feature:

Stops



Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0