NSN 5905-01-111-5187

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-111-5187 **Section Quantity: Body Style:** Cylindrical **Reliability Indicator:** Not established **Terminal Length:** 0.200 inches **Body Diameter:** 0.250 inches **Body Length:** 0.170 inches **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 230.0 **Center To Center Distance Between Terminals:** 0.200 inches **Terminal Location:** Rear end **Mounting Method: Terminal Electrical Resistance Per Section:** 5.000 kilohms single section **Rotary Actuator Travel In Angular Deg:** 230.0 **Center To Center Distance Between Center Terminal And Outside Terminal:** 0.100 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -100.0/+100.0 single section **Power Dissipation Rating Per Section In Watts:** 0.25 free air single section **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section

Actuator Travel Control Feature: Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 85.0 single section **Standard Taper Curve Per Section:** A single section

NSN 5905-01-111-5187

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia:

A002a0