NSN 5905-01-111-9400

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-111-9400 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 1.812 inches **Shaft Diameter:** Between 0.2487 inches and 0.2497 inches **Shaft Length:** Between 0.781 inches and 0.843 inches **Mounting Bushing Length:** 0.562 inches **Body Length:** 2.000 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Nonturn Device Location:** At 12 oclock **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Longitudinally positioned on the circumference **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 10.0 kilohms single section **Fixed Tap Quantity Per Section:** 2 single section **Tap Location From Ccw Terminal Per Section In Ohms:** 2000.0 single section and 8000.0 single section

Terminal Type And Quantity:

5 tab, solder lug

Shelf Life:

N/a

NSN 5905-01-111-9400

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A002a0