Nonprecision Wire Wound Variable Resistor - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5905-01-111-9400

## Section Quantity:

1

- Body Style:
- Cylindrical bushing mounted
- Reliability Indicator:
- Not established
- Body Diameter:
- 1.812 inches
- Shaft Diameter:
- Between 0.2487 inches and 0.2497 inches
- Shaft Length:
- Between 0.781 inches and 0.843 inches
- Mounting Bushing Length:
- 0.562 inches
- Body Length:
- 2.000 inches
- Shaft Style:
- Round
- Actuator Type:
- Single shaft
- Nonturn Device Location:
- At 12 oclock
- Screw Thread Diameter:
- 0.375 inches
- Screw Thread Series Designator:
- Unef
- Screw Thready Qty Per Inch (tpi):
- 32.0
- **Terminal Location:**
- Longitudinally positioned on the circumference

#### **Mounting Method:**

- Standard bushing
- **Electrical Resistance Per Section:**
- 10.0 kilohms single section

#### Fixed Tap Quantity Per Section:

2 single section

## Tap Location From Ccw Terminal Per Section In Ohms:

- 2000.0 single section and 8000.0 single section
- **Terminal Type And Quantity:**
- 5 tab, solder lug
- Shelf Life:
- N/a



# NSN 5905-01-111-9400

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0