NSN 5905-01-112-7458

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-112-7458 **Section Quantity: Body Style:** Cylindrical **Reliability Indicator:** Not established **Body Diameter:** 0.785 inches **Body Length:** 0.391 inches **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 270.0 **Maximum Starting Torque:** 10.00 inch-ounces **Maximum Running Torque:** 10.00 inch-ounces **Terminal Location:** Rear end **Mounting Method:** Tab **Electrical Resistance Per Section:** 1.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** 270.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 105.0 single section **Power Dissipation Rating Per Section In Watts:** 2.0 heat sink single section **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section **Actuator Travel Control Feature:** Stops Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 25.0 single section **Standard Taper Curve Per Section:** A single section

Terminal Type And Quantity:

3 tab, solder lug

NSN 5905-01-112-7458

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

Fiig:

A002a0