

View Online at <https://aerobasegroup.com/nsn/5905-01-112-7460>

Section Quantity:

2

Body Style:

Rectangular w/bushing

Reliability Indicator:

Not established

Shaft Diameter:

Between 0.248 inches and 0.250 inches

Shaft Length:

1.125 inches

Mounting Bushing Length:

0.375 inches

Body Length:

0.969 inches

Body Width:

0.625 inches

Body Height:

0.625 inches

Undercut Diameter:

0.125 inches

Shaft Style:

Round, stepped

Actuator Type:

Dual concentric

Effective Electrical Rotation In Deg Angular Rotation:

265.0

Maximum Starting Torque:

2.00 inch-ounces

Maximum Running Torque:

2.00 inch-ounces

Undercut Length:

0.250 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

20.0 kilohms all sections

Rotary Actuator Travel In Angular Deg:

300.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 all sections

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-1000.0/+1000.0 all sections

Power Dissipation Rating Per Section In Watts:

0.5 free air all sections

Resistance Tolerance Per Section In Percent:

-20.0/+20.0 all sections

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 all sections

Standard Taper Curve Per Section:

A all sections

Special Features:

Screwdriver slot adjustment

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0