Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-112-9174

## Section Quantity:

1

Body Style:

Cylindrical

## **Reliability Indicator:**

Not established

#### **Body Diameter:**

0.594 inches

#### **Body Length:**

0.156 inches

#### Actuator Type:

Flush drive with slot-hole

#### Effective Electrical Rotation In Deg Angular Rotation:

260.0

#### **Terminal Location:**

Radially positioned over more than half the circumference

## Mounting Method:

Terminal

#### **Electrical Resistance Per Section:**

25.000 kilohms single section

## Rotary Actuator Travel In Angular Deg:

260.0

#### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

85.0 single section

#### **Power Dissipation Rating Per Section In Watts:**

0.25 free air single section

#### **Resistance Tolerance Per Section In Percent:**

-20.0/+20.0 single section

#### Actuator Travel Control Feature:

Stops

#### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

55.0 single section

#### Standard Taper Curve Per Section:

A single section

## **Terminal Type And Quantity:**

3 tab, solder lug

#### Shelf Life:

N/a

## Unit Of Measure:

--

#### Demilitarization:

No

# NSN 5905-01-112-9174 Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2

AeroBase Group

Fiig: A002a0