NSN 5905-01-113-0503

Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-113-0503

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: 15.000 kilohms Resistance: 15.000 kilohms Resistance Tolerance In Percent: 25.00 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Quantity: 6 Terminal Type: Pin Reliability Indicator: Not established Terminal Length: 0.085 inches Body Length: 0.386 inches Body Length: 0.386 inches Body Width: 0.396 inches Body Height: 0.350 inches Schematic Diagram Designator: Balanced ladder network Power Dissipation Rating in Watts: 1.500 total network Identical Value Resistor Quantity: 3 each resistor Style Designator: Single inline Test Data Document:
Electrical Resistance: 15.000 kilohms Resistance Tolerance in Percent: -2.0004-2.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 125.0 Ambient Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.04-125.0 Inclosure Method: Encapsulated Terminal Quantity: 6 Terminal Type: Pin Reliability Indicator: Not established Terminal Length: 0.085 inches Body Length: 0.584 inches Body Width: 0.095 inches Body Width: 0.350 inches Body Height: 0.350 inches Belanced ladder network Power Dissipation Rating in Watts: 1.500 total network Identical Value Resistor Quantity: 3 each resistor Slyle Designator:
15.000 kilohms Resistance Tolerance In Percent: -2.000/-2.000 Ambient Tempurature In Deg Celsius At Full Rated Power: -2.5.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: -2.5.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: -2.5.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -5.5.0/+125.0 Inclosure Method:
Resistance Tolerance in Percent: -2.000/42.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/+125.0 Tempurature Method: Encapsulated Terminal Quantity: 6 Terminal Type: Pin Reliability Indicator: Not established Terminal Length: 0.085 inches Body Length: 0.085 inches Body Width: 0.095 inches Body Height: 0.350 inches Schematic Diagram Designator: Balanced ladder network Power Dissipation Rating in Watts: 1.500 total network Identical Value Resistor Quantity: 3 each resistor Stiple inline Test Data Document:
-2.000/+2.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Quantity: 6 Terminal Quantity: 7 Terminal Type: Pin Reliability Indicator: Not established Terminal Length: 0.085 inches Body Length: 0.584 inches Body Width: 0.095 inches Body Width: 0.095 inches Schematic Diagram Designator: Balanced ladder network Power Dissipation Rating In Watts: 1.500 total network Identical Value Resistor Quantity: 3 each resistor Skyle Designator: Single inline Test Data Document:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55,0/+125.0 Inclosure Method: Encapsulated Terminal Quantity: 6 7 Terminal Type: Pin Reliability Indicator: Not established Terminal Length: 0.085 inches Body Length: 0.085 inches Body Length: 0.350 inches Body Height: 0.350 inches Schematic Diagram Designator: Balanced ladder network Power Dissipation Rating In Watts: 1.500 total network Identical Value Resistor Quantity: 3 each resistor Stople Designator: Single inline Test Data Document:
25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Quantity: 6 Terminal Type: Pin Reliability Indicator: Not established Terminal Length: 0.085 inches Body Length: 0.884 inches Body Width: 0.985 inches Body Width: 0.985 inches Body Width: 0.985 inches Body Height: 0.350 inches Body Height: 0.350 inches Body Length: 0.350 inches Body Height: 0.350 inches Body Height: 0.350 inches Body Height: 0.350 inches Schematic Diagram Designator: Balanced ladder network Power Dissipation Rating In Watts: 1.500 total network Power Resistor Quantity: 3 each resistor Style Designator: Single inline Test Data Document:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Quantity: 6 Terminal Type: Pin Reliability Indicator: Not established Terminal Length: 0.085 inches Body Length: 0.584 inches Body Width: 0.095 inches Body Height: 0.350 inches Schematic Diagram Designator: Balanced ladder network Power Dissipation Rating in Watts: 1.500 total network Identical Value Resistor Quantity: 3 each resistor Style Designator: Single inline Test Data Document:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapulated Terminal Quantity: 6 Terminal Type: Pin Reliability Indicator: Not established Terminal Length: 0.085 inches Body Length: 0.085 inches Body Width: 0.095 inches Body Width: 0.350 inches Body Height: 0.350 inches Schematic Diagram Designator: Balanced ladder network Power Dissipation Rating In Watts: 1.500 total network Identical Value Resistor Quantity: 3 each resistor Style Designator: Single inline Test Data Document:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Quantity: 6 Terminal Type: Pin Reliability Indicator: Not established Terminal Length: 0.085 inches Body Length: 0.584 inches Body Width: 0.095 inches Body Height: 0.350 inches Body Height: 0.350 inches Schematic Diagram Designator: Balanced ladder network Power Dissipation Rating In Watts: 1.500 total network Identical Value Resistor Quantity: 3 sach resistor Style Designator: Single inline Test Data Document:
-56.0/+125.0 Inclosure Method: Encapsulated Terminal Quantity: 6 Terminal Type: Pin Reliability Indicator: Not established Terminal Length: 0.085 inches Body Length: 0.584 inches Body Width: 0.095 inches Body Width: 0.095 inches Body Height: 0.350 inches Body Leight: 0.350 inches Chematic Diagram Designator: Balanced ladder network Power Dissipation Rating in Watts: 1.500 total network Identical Value Resistor Quantity: 3 each resistor Style Designator: Single inline Test Data Document:
Inclosure Method: Encapsulated Terminal Quantity: 6 Terminal Type: Pin Reliability Indicator: Not established Terminal Length: 0.085 inches Body Length: 0.584 inches Body Width: 0.095 inches Body Height: 0.350 inches Bodhematic Diagram Designator: Balanced ladder network Power Dissipation Rating In Watts: 1.500 total network Identical Value Resistor Quantity: 3 each resistor Style Designator: Single inline Test Data Document:
Encapsulated Terminal Quantity: 6 Terminal Type: Pin Reliability Indicator: Not established Terminal Length: 0.085 inches Body Length: 0.584 inches Body Width: 0.095 inches Body Height: 0.350 inches Schematic Diagram Designator: Balanced ladder network Power Dissipation Rating In Watts: 1.500 total network Identical Value Resistor Quantity: 3 each resistor Style Designator: Single inline Test Data Document:
Terminal Quantity: 6 Terminal Type: Pin Reliability Indicator: Not established Terminal Length: 0.085 inches Body Length: 0.584 inches Body Width: 0.095 inches Body Height: 0.350 inches Schematic Diagram Designator: Balanced ladder network Power Dissipation Rating In Watts: 1.500 total network Identical Value Resistor Quantity: 3 each resistor Style Designator: Single inline Test Data Document:
Terminal Type: Pin Reliability Indicator: Not established Terminal Length: 0.085 inches Body Length: 0.584 inches Body Width: 0.095 inches Body Height: 0.350 inches Schematic Diagram Designator: Balanced ladder network Power Dissipation Rating In Watts: 1.500 total network Identical Value Resistor Quantity: 3 each resistor Style Designator: Single inline Test Data Document:
Terminal Type: Pin Reliability Indicator: Not established Terminal Length: 0.085 inches Body Length: 0.584 inches Body Width: 0.095 inches Body Height: 0.350 inches Schematic Diagram Designator: Balanced ladder network Power Dissipation Rating In Watts: 1.500 total network Identical Value Resistor Quantity: 3 each resistor Style Designator: Single inline Test Data Document:
Pin Reliability Indicator: Not established Terminal Length: 0.085 inches Body Length: 0.584 inches Body Width: 0.095 inches Body Height: 0.350 inches Schematic Diagram Designator: Balanced ladder network Power Dissipation Rating In Watts: 1.500 total network Identical Value Resistor Quantity: 3 each resistor Style Designator: Single inline Test Data Document:
Reliability Indicator: Not established Terminal Length: 0.085 inches Body Length: 0.584 inches Body Width: 0.095 inches Body Height: 0.350 inches Schematic Diagram Designator: Balanced ladder network Power Dissipation Rating In Watts: 1.500 total network Identical Value Resistor Quantity: 3 each resistor Style Designator: Single inline Test Data Document:
Not established Terminal Length: 0.085 inches Body Length: 0.584 inches Body Width: 0.095 inches Body Height: 0.350 inches Schematic Diagram Designator: Balanced ladder network Power Dissipation Rating In Watts: 1.500 total network Identical Value Resistor Quantity: 3 each resistor Style Designator: Single inline Test Data Document:
Terminal Length: 0.085 inches Body Length: 0.584 inches Body Width: 0.095 inches Body Height: 0.350 inches Schematic Diagram Designator: Balanced ladder network Power Dissipation Rating In Watts: 1.500 total network Identical Value Resistor Quantity: 3 each resistor Style Designator: Single inline Test Data Document:
Body Length: 0.584 inches Body Width: 0.095 inches Body Height: 0.350 inches Body Height: 0.350 inches Schematic Diagram Designator: Balanced ladder network Power Dissipation Rating In Watts: 1.500 total network Identical Value Resistor Quantity: 3 each resistor Style Designator: Single inline Test Data Document:
Body Length: 0.584 inches Body Width: 0.095 inches Body Height: 0.350 inches Schematic Diagram Designator: Balanced ladder network Power Dissipation Rating In Watts: 1.500 total network Identical Value Resistor Quantity: 3 each resistor Style Designator: Single inline Test Data Document:
0.584 inches Body Width: 0.095 inches Body Height: 0.350 inches Schematic Diagram Designator: Balanced ladder network Power Dissipation Rating In Watts: 1.500 total network Identical Value Resistor Quantity: 3 each resistor Style Designator: Single inline Test Data Document:
Body Width: 0.095 inches Body Height: 0.350 inches Schematic Diagram Designator: Balanced ladder network Power Dissipation Rating In Watts: 1.500 total network Identical Value Resistor Quantity: 3 each resistor Style Designator: Single inline Test Data Document:
0.095 inches Body Height: 0.350 inches Schematic Diagram Designator: Balanced ladder network Power Dissipation Rating In Watts: 1.500 total network Identical Value Resistor Quantity: 3 each resistor Style Designator: Single inline Test Data Document:
Body Height: 0.350 inches Schematic Diagram Designator: Balanced ladder network Power Dissipation Rating In Watts: 1.500 total network Identical Value Resistor Quantity: 3 each resistor Style Designator: Single inline Test Data Document:
0.350 inches Schematic Diagram Designator: Balanced ladder network Power Dissipation Rating In Watts: 1.500 total network Identical Value Resistor Quantity: 3 each resistor Style Designator: Single inline Test Data Document:
Schematic Diagram Designator: Balanced ladder network Power Dissipation Rating In Watts: 1.500 total network Identical Value Resistor Quantity: 3 each resistor Style Designator: Single inline Test Data Document:
Balanced ladder network Power Dissipation Rating In Watts: 1.500 total network Identical Value Resistor Quantity: 3 each resistor Style Designator: Single inline Test Data Document:
Power Dissipation Rating In Watts: 1.500 total network Identical Value Resistor Quantity: 3 each resistor Style Designator: Single inline Test Data Document:
1.500 total network Identical Value Resistor Quantity: 3 each resistor Style Designator: Single inline Test Data Document:
Identical Value Resistor Quantity: 3 each resistor Style Designator: Single inline Test Data Document:
3 each resistor Style Designator: Single inline Test Data Document:
Style Designator: Single inline Test Data Document:
Single inline Test Data Document:
Test Data Document:
81755-c8744 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.:
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Shelf Life:
N/a
Unit Of Measure:

__

NSN 5905-01-113-0503

Film Fixed Resistor Network - Page 2 of 2



Demilitarization:

No

Fiig:

A001a0