NSN 5905-01-114-0501

Film Fixed Resistor - Page 1 of 1

A001a0



View Online at https://aerobasegroup.com/nsn/5905-01-114-0501

200.0/+200.0 Electrical Resistance: 910.000 kilohms Resistance Tolerance in Percent: -2.000/+2.000 Ambient Tompurature in Deg Celsius At Full Rated Power: 70.0 Ambient Tompurature in Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: -1.625 inches Body Diameter: -0.336 inches Body Length: -0.728 inches Power Dissipation Rating in Watts: -2.000 free air Style Designator:	Tompurature Coefficient Of Resistance In Pom Per Dea Coloius
Electrical Resistance: 910.000 klohms Resistance Tolerance In Percent: 2000/4-2000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.825 inches Body Diameter: 0.336 inches Body Diameter: 0.326 inches Body Length: 0.728 inches Body Length: 0.728 inches Rower Dissipation Rating in Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil+-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil+-22684/8 government specification Sheff Life: N/a Unit Of Measure:	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
8 Resistance Tolerance In Percent: -2.000/4.2000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 170.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 170.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 170.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/4150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.625 inches Body Diameter: 0.336 inches Body Diameter: 0.326 inches Body Length: 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milt-722684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-milt-722684/8 government specification Sheff Life: Na Unit Of Measure: Demilitarization: No	
Resistance Tolerance In Percent: 2,00042,000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/4150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: -1.6.25 inches Body Diameter: -0.336 inches Body Length: -0.728 inches Body Length: -0.728 inches Solver Includes arise and State	
-2.000/42.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.625 inches Body Diameter: 0.336 inches Body Diameter: 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Syle Designator: 81494-mil22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 81349-mil226848 government specification Shelf Life: Na Unit Of Measure: - Demilitarization: No	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 180.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.625 inches Body Diameter: 0.336 inches Body Length: 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Tests Data Document: 81349-mil+-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil+-226848 government specification Shelf Life: Na Unit Of Measure: - Demilitarization: No	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: -1.625 inches Body Diameter: -0.336 inches Body Length: -0.728 inches Power Dissipation Rating in Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format: excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-22684/8 government specification Shelf Life: N/a Unit Of Measure: - Demilitarization: No	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.625 inches Body Diameter: 0.336 inches Body Length: 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mili22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 81349-mili22684/8 government specification Sheft Life: N/a Unit Of Measure: Demilitarization: No	
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.04-150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: -1.625 inches Body Diameter: 0.336 inches Body Length: 0.728 inches Body Length: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mill-r-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-22684/8 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No	
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: -1.625 inches Body Diameter: 0.336 inches Body Diameter: 0.726 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milt-r-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "', etc.). Specification Data: 81349-milt-r-22684/8 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No	
-55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.625 inches Body Diameter: 0.336 inches Body Length: 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "', etc.). Specification Data: 81349-milr-22684/8 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No	
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.625 inches Body Diameter: 0.336 inches Body Length: 0.728 inches Body Length: 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-22684/8 government specification No Unit Of Measure: Demilitarization: No	
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.625 inches Body Diameter: 0.336 inches Body Length: 0.728 inches Body Length: 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-22684/8 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No	-55.0/+150.0
Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.625 inches Body Diameter: 0.336 inches Body Length: 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-milr-22684/8 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No	Inclosure Method:
Wire lead Reliability Indicator: Not established Terminal Length: 1.625 inches Body Diameter: 0.336 inches Body Length: 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-22684/8 government specification Shelf Life: N/a Unit Of Measure: — Demilitarization: No	Encapsulated
Reliability Indicator: Not established Terminal Length: 1.625 inches Body Diameter: 0.336 inches Body Length: 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.) Specification Data: 81349-mil-r-22684/8 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No	Terminal Type:
Note established Terminal Length: 1.625 inches Body Diameter: 0.336 inches Body Length: 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-22684/8 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No	Wire lead
Terminal Length: 1.625 inches Body Diameter: 0.336 inches Body Length: 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-22684/8 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No	Reliability Indicator:
1.625 inches Body Diameter: 0.336 inches Body Length: 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-22684/8 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No	Not established
Body Diameter: 0.336 inches Body Length: 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-22684/8 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No	Terminal Length:
0.336 inches Body Length: 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-22684/8 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No	1.625 inches
Body Length: 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-22684/8 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No	Body Diameter:
0.728 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-22684/8 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No	0.336 inches
Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-22684/8 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No	Body Length:
2.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-22684/8 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No	0.728 inches
Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-22684/8 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No	Power Dissipation Rating In Watts:
Axial terminal each end Test Data Document: 81349-mil-r-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-22684/8 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No	2.000 free air
Test Data Document: 81349-mil-r-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-22684/8 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No	Style Designator:
81349-mil-r-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-22684/8 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No	Axial terminal each end
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-22684/8 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No	Test Data Document:
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-22684/8 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No	81349-mil-r-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
Specification Data: 81349-mil-r-22684/8 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No	format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
81349-mil-r-22684/8 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No	environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life: N/a Unit Of Measure: Demilitarization: No	Specification Data:
N/a Unit Of Measure: Demilitarization: No	81349-mil-r-22684/8 government specification
Unit Of Measure: Demilitarization: No	Shelf Life:
Demilitarization: No	N/a
No	Unit Of Measure:
No	
No	Demilitarization:
Fiig:	Fiig: