NSN 5905-01-114-5116

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-114-5116 **Section Quantity:** 2 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 2.8750 inches Pilot Length: 0.0620 inches **Overall Length:** 2.062 inches **Undercut Diameter:** 2.812 inches **Undercut Width:** 0.0730 inches **Body Diameter:** 3.000 inches **Shaft Diameter:** 0.2497 inches **Shaft Length:** 0.750 inches **Body Length:** 1.312 inches **Overall Diameter:** 3.380 inches **Mounting Lip Diameter:** 3.0000 inches **Mounting Lip Depth:** 0.0930 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 350.0 **Maximum Starting Torque:**

Maximum Starting Torque:
2.00 inch-ounces

Maximum Running Torque:

1.00 inch-ounces

NSN 5905-01-114-5116

Shaft End Play:

Precision Wire Wound Variable Resistor - Page 2 of 3



0.005 inches
Shaft Runout:
0.002 inches
Lateral Runout:
0.003 inches
Pilot Diameter Runout:
0.002 inches
Shaft Radial Play:
0.002 inches
Fragility Factor:
Moderately rugged
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Features Provided:
Humidity proof
Electrical Resistance Per Section:
500.0 ohms c and better finish
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-1.00/+1.00 all sections
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 all sections
Power Dissipation Rating Per Section In Watts:
6.0 7th secondary finish
Function Conformity Per Section:
All sections independent linearity
Resistance Tolerance Per Section In Percent:
-3.0/+3.0 all sections
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
All sections linear
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 all sections
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 all sections
Unpackaged Unit Weight:

Terminal surfaces gold

Precious Material And Location:

9.00 ounces

NSN 5905-01-114-5116

Precision Wire Wound Variable Resistor - Page 3 of 3



Precious Material:
Gold
Terminal Type And Quantity
6 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0