NSN 5905-01-114-8081

Precision Nonwire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-114-8081 **Section Quantity:** 3 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established First Flat Length: 0.375 inches Flat Height: 0.124 inches **Body Diameter:** 0.625 inches **Shaft Diameter:** 0.380 inches **Shaft Length:** 1.500 inches **Mounting Bushing Length:** 0.312 inches **Body Length:** 1.750 inches **Shaft Style:** Round, flatted **Shaft Bearing Type:** Sleeve Switch Type: Rotary **Switch Voltage Rating In Volts:** 115.0 **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 360.0 **Nonturn Device Location:** At 1 0clock **Nonturn Device Radius:** 0.250 inches **Shaft End Play:** 0.005 inches **Shaft Runout:**

0.002 inches **Lateral Runout:**0.002 inches

NSN 5905-01-114-8081

Precision Nonwire Wound Variable Resistor - Page 2 of 3



Shaft Radial Play:
0.002 inches
Switch Operating Position:
Start of linear movement
Switch Contact Arrangement:
Single pole, single throw, normally open, both positions maintained
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
22.0 kilohms all sections
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-1.00/+1.00 all sections
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 all sections
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-250.0/+250.0 all sections
Power Dissipation Rating Per Section In Watts:
0.5 free air all sections
Function Conformity Per Section:
All sections independent linearity
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 all sections
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
All sections linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 all sections
Switch Current Type And Rating In Amps:
1.000 ac
Terminal Type And Quantity:
10 turret

N/a

Shelf Life:

NSN 5905-01-114-8081

Precision Nonwire Wound Variable Resistor - Page 3 of 3



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A002a0