## NSN 5905-01-114-9791

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-114-9791 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 1.875 inches **Body Diameter:** 1.156 centimeters **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.875 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 0.812 inches **Overall Diameter:** 1.750 inches **Shaft Style:** Round Switch Type: Rotary **Switch Voltage Rating In Volts:** 125.0 **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 292.0 **Maximum Starting Torque:** 9.00 inch-ounces **Maximum Running Torque:** 9.00 inch-ounces

**Maximum Stop Torque:** 192.00 inch-ounces **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.531 inches

**Switch Operating Position:** 

Start of rotation

## NSN 5905-01-114-9791

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 3



Switch Contact Arrangement:
Single pole, single throw, normally open, both positions maintained
Fragility Factor:
Moderately rugged
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Rear-bottom
Mounting Method:
Standard bushing
Features Provided:
Switch
Electrical Resistance Per Section:
10.0 percent, rated amperes c and better flooring
Rotary Actuator Travel In Angular Deg:
333.0
Resistance Tempurature Characteristic Range Per Section In Percent:
+0.0/+8.8 -55 degrees celsius single section and +0.0/+6.9 120 degrees celsius single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Power Dissipation Rating Per Section In Watts:
2.25 7th secondary quality
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Switch Current Type And Rating In Amps:
2.000 ac
Standard Taper Curve Per Section:
C single section
Terminal Type And Quantity:
5 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

## NSN 5905-01-114-9791

Nonprecision Nonwire Wound Variable Resistor - Page 3 of 3



Fiig:

A002a0