NSN 5905-01-115-4149

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-115-4149 **Section Quantity:** 1 **Body Style:** Rectangular w/bushing **Reliability Indicator:** Not established **Overall Length:** 1.613 inches **Shaft Diameter:** 0.110 inches **Shaft Length:** 0.070 inches **Mounting Bushing Length:** 0.285 inches **Body Length:** 1.328 inches **Body Width:** 0.266 inches **Body Height:** 0.391 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 7920.0 **Maximum Starting Torque:** 5.00 inch-ounces **Maximum Running Torque:** 5.00 inch-ounces **Fragility Factor:** Moderately delicate **Screw Thread Diameter:** 0.190 inches **Screw Thread Series Designator:** Unf Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:**

Rear end

Mounting Method: Standard bushing

NSN 5905-01-115-4149

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
200.0 ohms c and better flooring
Rotary Actuator Travel In Angular Deg:
7920.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
175.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-50.0/+50.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 7th secondary quality
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0