NSN 5905-01-115-9367

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-115-9367 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established First Flat Length: 0.530 inches Flat Height: Between 0.153 inches and 0.157 inches **Body Diameter:** Between 0.825 inches and 0.850 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.620 inches **Body Length:** 0.420 inches **Shaft Style:** Round, flatted **Actuator Type:** Single shaft **Maximum Starting Torque:** 12.00 inch-ounces **Maximum Running Torque:** 12.00 inch-ounces **Terminal Location:** Rear end **Mounting Method:** Tab Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -800.0/+800.0 single section **Power Dissipation Rating Per Section In Watts:** 2.0 free air single section **Resistance Tolerance Per Section In Percent:** -20.0/+20.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life:

N/a

NSN 5905-01-115-9367

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A002a0