## NSN 5905-01-116-4794

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-116-4794

Section Quantity:
1
Body Style:
Cylindrical
Reliability Indicator:
Not established
Terminal Length:
0.180 inches
Body Diameter:
0.375 inches
Body Length:
0.200 inches
Actuator Type:
Integral knob
Effective Electrical Rotation In Deg Angular Rotation:
190.0
Maximum Starting Torque:
6.00 inch-ounces
Center To Center Distance Between Terminals:
0.200 inches
Fragility Factor:
Rugged
Terminal Location:
Rear end
Mounting Method:
Terminal
Electrical Resistance Per Section:
2.0 megohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.100 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-100.0/+100.0 single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
-20.0/+20.0 single section
Actuator Travel Control Feature:
Stops

## NSN 5905-01-116-4794

Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No