NSN 5905-01-116-8823

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-116-8823

Section Quantity:
1
Body Style:
Rectangular
Reliability Indicator:
Not established
Shaft Diameter:
Between 0.250 inches and 0.350 inches
Shaft Length:
1.070 inches
Body Length:
0.550 inches
Body Width:
Between 0.945 inches and 1.015 inches
Body Height:
Between 1.225 inches and 1.292 inches
Shaft Style:
Round
Actuator Type:
Double ended shaft
Nonturn Device Location:
At 3 oclock and at 9 oclock and at 12 oclock
Nonturn Device Radius:
0.596 inches
Fragility Factor:
Moderately rugged
Terminal Location:
Rear end
Mounting Method:
Tab
Features Provided:
Humidity proof
Electrical Resistance Per Section:
20.0 megohms single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
105.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-100.0/+300.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-20.0/+20.0 single section

NSN 5905-01-116-8823

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
55.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a

Demilitarization:

Unit Of Measure:

No

Fiig:

A002a0