NSN 5905-01-117-2709

-50.0/+50.0

4.320 ohms

-1.000/+1.000

25.0

Electrical Resistance:

Resistance Tolerance In Percent:

Inductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-117-2709

Ambient Tempurature In Deg Celsius At Full Rated Power:

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: |
|--|
| 275.0 |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius: |
| -55.0/+275.0 |
| Inclosure Method: |
| Encased |
| Terminal Type: |
| Tab, solder lug |
| Reliability Indicator: |
| Established |
| Reliability Failure Rate Level In Percent: |
| 1.000 |
| Terminal Length: |
| 0.312 inches |
| Body Length: |
| 0.750 inches |
| Body Width: |
| 0.438 inches |
| Body Height: |
| 0.406 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |
| 0.562 inches |
| Power Dissipation Rating In Watts: |
| 10.000 heat sink |
| Mounting Hole Size: |
| 0.094 inches |
| Style Designator: |
| Axial terminal (s) |
| Test Data Document: |
| 81349-mil-r-39009/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| |

NSN 5905-01-117-2709

Inductive Wire Wound Fixed Resistor - Page 2 of 2



Demilitarization:

No

Fiig:

A001a0