NSN 5905-01-118-0063

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-118-0063

Section Quantity:
1
Body Style:
Rectangular
Reliability Indicator:
Not established
Overall Length:
0.300 inches
Terminal Length:
0.188 inches
Overall Height:
0.543 inches
Overall Width:
0.312 inches
Body Length:
0.300 inches
Body Width:
0.312 inches
Body Height:
0.355 inches
Shaft Bearing Type:
Bearing
Actuator Type:
Flush drive with slot-hole
Maximum Running Torque:
5.00 inch-ounces
Maximum Stop Torque:
15.00 inch-ounces
Center To Center Distance Between Terminals:
0.200 inches
Fragility Factor:
Moderately rugged
Terminal Location:
Lower adjacent side single row
Mounting Method:
Terminal
Cubic Measure:
0.051 cubic inches
Electrical Resistance Per Section:
25.000 kilohms single section
Rotary Actuator Travel In Angular Deg:

285.0

NSN 5905-01-118-0063

No Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Center To Center Distance Between Center Terminal And Outside Terminal: 0.100 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section **Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:** -150.0/+150.0 single section **Power Dissipation Rating Per Section In Watts:** 0.5 free air single section **Resistance Tolerance Per Section In Percent:** -20.0/+20.0 single section **Actuator Travel Control Feature:** Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 85.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 pin Shelf Life: N/a **Unit Of Measure:** Demilitarization: