NSN 5905-01-118-1470

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-118-1470 **Section Quantity: Body Style:** Rectangular w/mounting holes **Reliability Indicator:** Not established **Overall Length:** 0.535 inches **Overall Height:** 0.500 inches **Overall Width:** 0.187 inches **Mounting Hole Diameter:** 0.093 inches **Shaft Diameter:** 0.078 inches **Shaft Length:** 0.035 inches **Body Length:** 0.500 inches **Body Width:** 0.187 inches **Body Height:** 0.500 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 16200.0 **Maximum Starting Torque:**

5.00 inch-ounces **Maximum Running Torque:** 5.00 inch-ounces **Lateral Distance Between Mounting Hole Centers:** 0.520 inches **Mounting Facility Quantity:** 2 **Terminal Location:** Rear end **Mounting Method:** Unthreaded hole

NSN 5905-01-118-1470

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Features Provided:
Humidity proof
Electrical Resistance Per Section:
25.0 percent, rated amperes c and better flooring
Rotary Actuator Travel In Angular Deg:
7200.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
100.0/+100.0 single section
Power Dissipation Rating Per Section In Watts:
0.5 7th secondary quality
Resistance Tolerance Per Section In Percent:
10.0/+10.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
35.0 single section
Standard Taper Curve Per Section:
A single section
Test Data Document:
31349-mil-r-22097 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
3 wire lead
Specification Data:
31349-mil-r-22097/3 government specification
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
4002a0