NSN 5905-01-118-9064

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-118-9064

Section Quantity:
4
Body Style:
Rectangular
Reliability Indicator:
Not established
Body Length:
0.190 inches
Body Width:
0.250 inches
Body Height:
0.880 inches
Actuator Type:
Flush drive with slot-hole
Effective Electrical Rotation In Deg Angular Rotation:
230.0
Maximum Starting Torque:
2.00 inch-ounces
Maximum Running Torque:
2.00 inch-ounces
Terminal Location:
Dual inline
Mounting Method:
Terminal
Electrical Resistance Per Section:
1.0 kilohms all sections
Rotary Actuator Travel In Angular Deg:
360.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 all sections
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-100.0/+100.0 all sections
Power Dissipation Rating Per Section In Watts:
0.5 free air all sections
Resistance Tolerance Per Section In Percent:
-20.0/+20.0 all sections
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 all sections
Standard Taper Curve Per Section:

A all sections

NSN 5905-01-118-9064

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Special Features:
Four units in dip
Terminal Type And Quantity:
16 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0