

View Online at <https://aerobasegroup.com/nsn/5905-01-119-8014>

**Section Quantity:**

1

**Body Style:**

Cylindrical

**Reliability Indicator:**

Not established

**Body Diameter:**

0.780 inches

**Body Length:**

0.560 inches

**Actuator Type:**

Flush drive with slot-hole

**Effective Electrical Rotation In Deg Angular Rotation:**

270.0

**Maximum Starting Torque:**

10.00 inch-ounces

**Maximum Running Torque:**

10.00 inch-ounces

**Fragility Factor:**

Rugged

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Tab and terminal

**Electrical Resistance Per Section:**

1.0 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

360.0

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

105.0 single section

**Power Dissipation Rating Per Section In Watts:**

2.0 heat sink single section

**Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

**Actuator Travel Control Feature:**

Stops

**Temperature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:**

-20.0/+20.0 single section

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

25.0 single section

**Standard Taper Curve Per Section:**

A single section

**Special Features:**

Heavy tension contactor 115n-7

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0