NSN 5905-01-120-1426

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-120-1426 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 0.875 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.312 inches **Mounting Stud Length:** 0.062 inches **Mounting Bushing Length:** 0.812 inches **Body Length:** 0.750 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3600.0 **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Mounting Facility Quantity: Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Locking bushing **Electrical Resistance Per Section:** 1.000 megohms single section

Rotary Actuator Travel In Angular Deg: 3600.0

Power Dissipation Rating Per Section In Watts:

2.0 free air single section

NSN 5905-01-120-1426

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



| Resistance | Tolerance | Per Section | In Percent |
|------------|-----------|--------------------|------------|
| | | | |

-5.0/+5.0 single section

Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:

-20.0/+20.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0