Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-120-9043

# Section Quantity:

1

Body Style:

Rectangular

**Reliability Indicator:** 

Not established

## **Terminal Length:**

0.200 inches

**Body Length:** 

0.190 inches

**Body Width:** 

#### 0.375 inches

Body Height:

#### 0.375 inches

Actuator Type:

## Flush drive with slot-hole

## Effective Electrical Rotation In Deg Angular Rotation:

280.0

## Maximum Starting Torque:

5.00 inch-ounces

# Maximum Running Torque:

5.00 inch-ounces

# Center To Center Distance Between Terminals:

0.300 inches

# **Terminal Location:**

Lower adjacent side single row

#### Mounting Method:

Terminal

## **Electrical Resistance Per Section:**

1.0 megohms single section

## **Rotary Actuator Travel In Angular Deg:**

360.0

# Center To Center Distance Between Center Terminal And Outside Terminal:

0.150 inches

# Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

# Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-150.0/+150.0 single section

# Power Dissipation Rating Per Section In Watts:

0.5 free air single section

# **Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

# NSN 5905-01-120-9043

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



**Actuator Travel Control Feature:** 

Stops

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0