## NSN 5905-01-121-2142

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-121-2142

Section Quantity:
1
Body Style:
Rectangular w/mounting holes/slots
Reliability Indicator:
Not established
Overall Length:
1.320 inches
Terminal Length:
0.500 inches
Overall Height:
0.825 inches
Overall Width:
0.195 inches
Mounting Hole Diameter:
0.093 inches
Shaft Diameter:
0.125 inches
Shaft Length:
0.070 inches
Body Length:
1.250 inches
Body Width:
0.195 inches
Body Height:
0.325 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
9000.0
Maximum Starting Torque:
5.00 inch-ounces
Maximum Running Torque:
5.00 inch-ounces
Center To Center Distance Between Terminals:
0.700 inches
Lateral Distance Between Mounting Hole Centers:
1.000 inches
Mounting Facility Quantity:

## NSN 5905-01-121-2142

A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Terminal Location:
Lower adjacent side two rows
Mounting Method:
Terminal and unthreaded hole
Center To Center Distance Between Terminal Rows:
0.100 inches
Features Provided:
Humidity proof
Electrical Resistance Per Section:
10.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
9000.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.300 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-10.0/+10.0 single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Clutch
Criticality Code Justification:
Feat
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 single section
Standard Taper Curve Per Section:
A single section
Special Features:
Item must comply with requirements of defense electronics supply center production standard no. L03120; for navy nuclear propulsion plan
products only
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: