

View Online at <https://aerobasegroup.com/nsn/5905-01-121-2260>

Section Quantity:

1

Body Style:

Rectangular

Reliability Indicator:

Not established

Overall Length:

0.435 inches

Terminal Length:

0.180 inches

Overall Height:

0.540 inches

Overall Width:

0.245 inches

Shaft Diameter:

0.090 inches

Shaft Length:

0.060 inches

Body Length:

0.375 inches

Body Width:

0.375 inches

Body Height:

0.245 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

6480.0

Maximum Starting Torque:

5.00 inch-ounces

Maximum Running Torque:

5.00 inch-ounces

Center To Center Distance Between Terminals:

0.200 inches

Fragility Factor:

Moderately rugged

Terminal Location:

Lower adjacent side single row

Mounting Method:

Terminal

Features Provided:

Humidity proof

Electrical Resistance Per Section:

100.0 percent, rated amperes c and better flooring

Rotary Actuator Travel In Angular Deg:

6480.0

Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0/+100.0 single section

Power Dissipation Rating Per Section In Watts:

0.5 7th secondary quality

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Clutch

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0