NSN 5905-01-121-9324

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-121-9324

Electrical Resistance: 487.000 ohms Resistance Tolerance In Percent:	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+105.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: -1.500 inches Body Length: -0.250 inches Power Dissipation Rating in Watts: -0.250 inches Power Dissipation Rating in Watts: -0.250 free air Style Designator:	-250.0/+250.0
Resistance Tolerance in Percent: -1.000/+1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/+105.0 Inclosure Method: -Encapsulated Terminal Type: Wire Island Reliability Indicator: Not established Terminal Length: -1.500 inches Body Diameter: -0.250 inches Body Length: -0.250 inches Power Dissipation Rating in Watts: -0.250 inches Style Designator:	Electrical Resistance:
Annibient Tempurature in Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 155.0/±105.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1,000 inches Body Diameter: 0,009 inches Body Diameter: 0,009 inches Body Dissipation Rating in Watts: 0,250 inches Power Dissipation Rating in Watts: 0,250 free air Style Designator: Axial terminal each end Test Data Document: Style Designator: Style Designator: Axial terminal each end Test Data Document: Style Designator: Axial terminal each end Test Data Designator Test Data Designator Test Data Designator Test Data De	487.000 ohms
Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 150.0/+105.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: 0.090 inches Body Diameter: 0.090 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 64959-4820616 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: 84959-4820616 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: 84959-4820616 drawing (this is the document that may be referenced in a basic governing drawing) Shelf Life: No Demilitarization: No Filig:	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+105.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Dameter: 0.090 inches Body Dameter: 0.250 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Avial terminal each end Test Data Document: 54959-ks20616 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: No Unit Of Measure: — Demilitarization: No Filig:	-1.000/+1.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+105.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: 0.090 inches Body Diameter: 0.250 inches Power Dissipation Rating in Watts: 0.250 free air Style Designator: Akal terminal leach end Tests Data Document: 844959-ks20616 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: No Demilitarization: No Filig:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient In Deg Celsius:	70.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+105.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: 0.090 inches Body Diameter: 0.090 inches Body Displation Rating In Watts: 0.250 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 64959-ks20616 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: No Unit Of Measure:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Ferminal Length: 1.500 inches Body Diameter: 0.090 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.250 inches Style Designator: Axial terminal each end Test Data Document: 84959-ks20616 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: No Unit Of Measure:	150.0
Inclosure Method: Encapsulated Terminal Type: Wire lead Rediability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: 0.090 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Avaid terminal each end Test Data Document: 84959-ks20616 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 84959-ks20616 drawing (this is the basic governing drawing where the thing is the style of the style of the thing is the style of the st	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 Inches Body Diameter: 0.090 Inches Body Length: 0.250 Inches Power Dissipation Rating In Watts: 0.250 Inches Style Designator: Axial terminal each end Test Data Document: 64959+ks20616 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; sexuludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	-55.0/+105.0
Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: 0.090 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.250 finches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 64959-ks20616 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Filg:	Inclosure Method:
Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: 0.090 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 64959-ks20616 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: No Demilitarization: No Fig:	Encapsulated
Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: 0.090 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 64959-ks20616 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Filg:	Terminal Type:
Note established Terminal Length: 1.500 inches Body Diameter: 0.090 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 64959-ks20616 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Wire lead
Terminal Length: 1.500 inches Body Diameter: 1.0090 inches Body Length: 1.0.250 inches Power Dissipation Rating In Watts: 1.0.250 free air Style Designator: Axial terminal each end Test Data Document: 64959-ks20616 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	Reliability Indicator:
1.500 inches Body Diameter: 1.0090 inches Body Length: 1.0.250 inches Power Dissipation Rating In Watts: 1.0.250 free air Style Designator: Axial terminal each end Test Data Document: 64959-ks20616 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Not established
Body Diameter: 0.090 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 64959-ks20616 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Terminal Length:
Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 64959-ks20616 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	1.500 inches
Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 64959-ks20616 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Body Diameter:
Double Power Dissipation Rating In Watts: Double Designator: Axial terminal each end Test Data Document: 64959-ks20616 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	0.090 inches
Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 64959-ks20616 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Body Length:
O.250 free air Style Designator: Axial terminal each end Test Data Document: 64959-ks20616 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.250 inches
Style Designator: Axial terminal each end Test Data Document: 64959-ks20616 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Power Dissipation Rating In Watts:
Axial terminal each end Test Data Document: 64959-ks20616 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.250 free air
Test Data Document: 64959-ks20616 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	Style Designator:
64959-ks20616 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Axial terminal each end
excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Test Data Document:
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	64959-ks20616 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
N/a Unit Of Measure: Demilitarization: No Fiig:	excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Fiig:	N/a
No Filg:	Unit Of Measure:
No Filg:	
Fiig:	Demilitarization:
	No
A001a0	Fiig:
	A001a0