NSN 5905-01-122-4654

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-122-4654 **Section Quantity: Reliability Indicator:** Not established **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 290.0 **Maximum Starting Torque:** 7.00 inch-ounces **Maximum Running Torque:** 7.00 inch-ounces **Terminal Location:** Rear end **Features Provided:** Grounded contact arm **Electrical Resistance Per Section:** 10.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** 290.0 Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -500.0/+500.0 single section **Power Dissipation Rating Per Section In Watts:** 0.25 free air single section **Resistance Tolerance Per Section In Percent:** -20.0/+20.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 2 tab, solder lug Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Fiig:

A002a0