Nonprecision Nonwire Wound Variable Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-122-4655

Section Quantity:
1
Reliability Indicator: Not established
Actuator Type:
Flush drive with slot-hole
Effective Electrical Rotation In Deg Angular Rotation:
290.0
Maximum Starting Torque:
7.00 inch-ounces
Maximum Running Torque:
7.00 inch-ounces
Terminal Location:
Rear end
Features Provided:
Grounded contact arm
Electrical Resistance Per Section:
220.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
290.0
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-500.0/+500.0 single section
Power Dissipation Rating Per Section In Watts:
0.25 free air single section
Resistance Tolerance Per Section In Percent:
-20.0/+20.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
2 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Filg:
A002a0