

View Online at <https://aerobasegroup.com/nsn/5905-01-122-4677>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

3.481 inches

First Flat Length:

0.500 inches

Flat Height:

0.196 inches

Body Diameter:

1.750 inches

Shaft Diameter:

0.2495 inches

Shaft Length:

0.875 inches

Mounting Bushing Length:

0.375 inches

Body Length:

2.312 inches

Shaft Style:

Round, flatted

Shaft Bearing Type:

Bearing

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

3600.0

Maximum Starting Torque:

10.00 inch-ounces

Maximum Running Torque:

10.00 inch-ounces

Fragility Factor:

Rugged

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Rear end

Mounting Method:

Standard bushing w/shaft seal

Features Provided:

Humidity proof

Electrical Resistance Per Section:

5.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

3610.0

Function Conformity Tolerance Per Section:

-0.20/+0.20 single section

Power Dissipation Rating Per Section In Watts:

2.5 free air single section

Function Conformity Per Section:

Single section independent linearity

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 single section

Actuator Travel Control Feature:

Stops

Function Characteristic Per Section:

Single section linear

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Special Features:

Contact has precious metal tip

Test Data Document:

99167-5902523 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0